## Amendments to the Specification:

Please replace the Abstract with the following amended paragraph:

A computer system (20) with having a security domain (22), at least one client business domain (26), and a plurality of client terminals (34) utilizes a hidden link dynamic key manager (24, 84) and a database structure including that includes encrypted data entities (30C, 30D) and a security identification attribute (32) for storage of encrypted data. A method Methods for encryption, storage, decryption, and retrieval of encrypting data and for storing, decrypting, and retrieving encrypted data operates operate on the computer system (20), which also includes an information database (62) and a key database (44). The key database (44) is isolated from the information database (62). The hidden link key manager is stored in the security domain (22) and includes a system key manager (84) operable to generate system keys with system key common names and an encryption key manager (24) operable to generate encryption keys having encryption key identifications. The key managers (24, 84) operate on a key server (40), which is mirrored by a secondary key server (42). A general security manager (82) also operates on the key server (40) to control access to the security domain (22). The security information attribute (32) is stored with a persistent data entity (30A) that is associated with the other encrypted data entities (30C, 30D) by a database schema. The security information attribute (32) includes the encryption key identification (112) for the encryption key used to encrypt the data entities (30C, 30D). The encryption key identification is encrypted by the system key, and the The encryption key identification (112) for the encryption key used to encrypt the data entities (30C, 30D) is encrypted by a system key and then stored as part of the security information attribute (32). The system key common name hash value (114) is also stored in the security information attribute (32). The information data entities (30) are Appl. No. 09/693,605

Dated February 28, 2005

Reply to Office Action dated September 1, 2004

stored on the information database (62), but the encryption key identification (153), encryption key

(154), system key common name hash value (156, 157), and system key common name (158) are

stored in the key database (44) inside the security domain (22). The system key itself is stored on a

3

Smart Card reader (56) inside the security domain.

WA 792429-1